Puck Recessed

ARKOSLIGHT

DIMENSIONS



AWARDS

	PRODUCT
Name	PUCK RECESSED IP54 M 3000K WT
Reference	A3141011WT
Color	Textured white
RAL	9016
Category	CEILING RECESSED

	LIGHT SOURCE
Type	LED
Gross luminous flux	1160 lm
Colour temperature	3000 K
Chromatic stability	MacAdam Step 2
Colour Rendering Index	CRI>90
Power	9 W
Current	500 mA
Efficacy	129 lm/W
LED lifespan	L80B10 >60.000h

	LIGHTING FIXTURE | PHOTOMETRIC DATA
Lighting efficiency	80%
Light beam angle	45°

	LIGHTING FIXTURE | ELECTRICAL DATA
Driver	Included - Connected
Power values of the system	10,11 W
Voltage	220V/240V
Frecuency	50/60 Hz
Dimming	No Dim - Other DIM, please consult
Electrical insulation class	⧈

	OTHER DATA
Sealing	IP54
Wireless control	Please Consult
Emergency power supply	Please Consult
Recess measurements	Ø73 mm
Weight	326 g
Packaged weight	380 g
Packaging dimensions	158 x 156 x 59 mm
Units per package	1
Materials	Aluminium / Optical Glass

CE

Puck Recessed is the Puck version for recessed applications. Puck Recessed aims to fulfill the functions of general lighting. Its discreet presence takes the shape of a circular piece, totally made of aluminium, with a slight rounded slant to hold the light source back a few centimetres.

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com

25-04-24 / 01:27

5 Year GUARANTEE*

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR

ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	5.7	6.3	5.9	6.5	6.7	5.3	6.0	5.5	6.2	6.4
	3H	6.5	7.1	6.8	7.4	7.6	6.6	7.2	6.8	7.4	7.6
	4H	8.1	8.7	8.4	9.0	9.2	8.3	8.8	8.6	9.1	9.4
	6H	8.7	9.3	9.0	9.5	9.8	8.8	9.3	9.1	9.6	9.9
	8H	8.8	9.3	9.2	9.6	9.9	9.0	9.5	9.3	9.8	10.0
	12H	8.9	9.4	9.2	9.7	10.0	9.0	9.5	9.3	9.8	10.1
4H	2H	5.8	6.4	6.1	6.6	6.9	5.5	6.1	5.8	6.3	6.6
	3H	7.3	7.8	7.7	8.1	8.4	7.4	7.9	7.8	8.2	8.5
	4H	9.2	9.6	9.5	9.9	10.3	9.3	9.7	9.7	10.0	10.4
	6H	9.8	10.2	10.2	10.5	10.9	9.9	10.3	10.3	10.6	11.0
	8H	10.0	10.3	10.4	10.7	11.1	10.1	10.4	10.5	10.8	11.2
	12H	10.1	10.3	10.5	10.7	11.1	10.2	10.4	10.6	10.8	11.3
8H	4H	9.7	10.0	10.1	10.3	10.7	9.8	10.1	10.2	10.4	10.8
	6H	10.4	10.6	10.8	11.0	11.5	10.5	10.7	10.9	11.1	11.6
	8H	10.6	10.7	11.0	11.2	11.7	10.7	10.9	11.2	11.3	11.8
	12H	10.7	10.8	11.2	11.3	11.8	10.8	10.9	11.3	11.4	11.9
12H	4H	9.7	9.9	10.1	10.3	10.8	9.8	10.0	10.2	10.4	10.9
	6H	10.4	10.6	10.9	11.1	11.5	10.5	10.7	11.0	11.1	11.6
	8H	10.6	10.8	11.1	11.2	11.7	10.7	10.9	11.2	11.4	11.9
Variation of the observer position for the luminaire distances S											
S = 1.0H		+4.5 / -3.3					+4.7 / -3.4				
S = 1.5H		+7.2 / -4.1					+7.3 / -4.0				
S = 2.0H		+9.1 / -5.0					+9.2 / -4.8				
Standard table		BK01					BK01				
Correction Summand		-5.2					-5.1				
Corrected Glare Indices referring to 1160lm Total Luminous Flux											

ECODESIGN AND ENERGY LABELLING

ARKOSLIGHT®



Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann

Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES
INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL
INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT
ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI
ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN

Interrumpir la alimentación del aparato
Cut the power supply to the luminaire
Couper l'alimentation du luminaire
Interrompere l'alimentazione dell'apparecchio
Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho
Remove light source(s) for disposal
Retirer la (les) source(s) lumineuse(s) pour l'élimination
Rimuovere la/le sorgente/e di luce per lo smaltimento
Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho
Remove the battery for decommissioning
Retirer la batterie pour sa mise au rebut
Rimuovere la batteria per la dismissione
Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho
Remove control gear for disposal
Retirer le dispositif de commande pour l'élimination
Rimuovere l'alimentatore per lo smaltimento
Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE
Send the materials to a WEEE collection centre
Envoyer les matériaux dans une déchetterie DEEE
Inviare i materiali ad un centro di raccolta RAEE
Die Materialien in einem WEEE-Zentrum entsorgen



Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com

5 Year GUARANTEE