



Ref. Certif. No.

ES2234

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

FIXED GENERAL PURPOSE LUMINAIRES

Name and address of the applicant

ARKOSLIGHT, S.L.
PI EL OLIVERAL, CL. N
46394 RIBARROJA DEL TURIA (Valencia - Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark (if any)

ARKOSLIGHT

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

See references on the Annex

Additional information (if necessary may also be reported on page 2)

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-2-1:1979 + AMD1:1987
IEC 60598-1:2014
IEC 60598-1:2014/AMD1:2017

As shown in the Test Report Ref. No. which forms part of this Certificate

2016110738B1-M1, 2019060434B1, 2019050281B1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2019-07-12

Signature: 
Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2234

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Product: FIXED GENERAL PURPOSE LUMINAIRES
Trade Mark: ARKOSLIGHT

Type reference	Rated voltage and frequency	N° of lamps and rated wattage	Power supply connection means	Protection against electric shock (class)	Additional data
SIX L A239-0	48 V=	1 x 24,5 W max.	Terminals	Class III	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX L 1 A286-11	220-240 V~ 50/60 Hz	1 x 11,5 W max.	Track adaptor	Class II	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX L 2 A286-2	220-240 V~ 50/60 Hz	1 x 24,5 W max.	Track adaptor	Class II	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX M A330-0	48 V=	1 x 17 W max.	Terminals	Class III	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX M 1 A331-11	220-240 V~ 50/60 Hz	1 x 11,5 W max.	Track adaptor	Class II	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX M 2 A331-2	220-240 V~ 50/60 Hz	1 x 17 W max.	Track adaptor	Class II	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX S A333-0	48 V=	1 x 8,5 W max.	Terminals	Class III	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX XS A335-0	48 V=	1 x 4,5 W max.	Terminals	Class III	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX XS A335-1 DOUBLE	48 V=	2 x 4,5 W max.	Terminals	Class III	2700K, 3000K, 4000 K; non-dimmable and dimmable
SIX 1 A286-11	220-240 V~ 50/60 Hz	1 x 11,5 W max	Track adaptor	Class II	2700K, 3000K, 4000 K
SIX 2 A286-21	220-240 V~ 50/60 Hz	1 x 23 W max	Track adaptor	Class II	2700K, 3000K, 4000 K
ZEN LED 1 A183	220-240 V~ 50/60 Hz	1 x 12W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN LED 1 A283	220-240 V~ 50/60 Hz	1 x 12W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN LED 2 A183	220-240 V~ 50/60 Hz	1 x 17W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN LED 2 A283	220-240 V~ 50/60 Hz	1 x 17W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN LED 3 A183	220-240 V~ 50/60 Hz	1 x 23W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN LED 3 A283	220-240 V~ 50/60 Hz	1 x 23 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 1 A184	220-240 V~ 50/60 Hz	1 x 12 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 1 A284	220-240 V~ 50/60 Hz	1 x 12 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 2 A184	220-240 V~ 50/60 Hz	1 x 17 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 2 A284	220-240 V~ 50/60 Hz	1 x 17 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 3 A184	220-240 V~ 50/60 Hz	1 x 23 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE SURFACE 3 A284	220-240 V~ 50/60 Hz	1 x 23 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 1 A184	220-240 V~ 50/60 Hz	1 x 12 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 1 A284	220-240 V~ 50/60 Hz	1 x 12 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 2 A184	220-240 V~ 50/60 Hz	1 x 17 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 2 A284	220-240 V~ 50/60 Hz	1 x 17 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 3 A184	220-240 V~ 50/60 Hz	1 x 23 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable
ZEN TUBE 3 A284	220-240 V~ 50/60 Hz	1 x 23 W max	Terminals	Class II	3000K, 4000K; non-dimmable and dimmable

Type of lamps and lampholder: LED

Degree of protection (IP): IP 20

Class. respect supporting material: Suitable for normally flammable surfaces

Limitations: Horizontal fixing