



DIMENSIONS



ACCESORIES



TRACK 48V OPTIONS

AWARDS



| | |
|-----------|---|
| Name | SIX S 48V SHORT UL DIM DALI 34° 3000K NTW |
| Reference | U3330231NTW-S |
| Color | Textured black - White track |
| Category | Track Lights |

PRODUCT

| | |
|-----------------------|----------------|
| Type | LED |
| Gross luminous flux | 1140 Lm |
| Color temperature | 3000 K |
| Chromatic stability | MacAdam Step 2 |
| Color Rendering Index | CRI>90 |
| Power | 9 W |
| Efficacy | 127 Lm/W |
| LED lifespan | L80B10>60.000h |

LIGHT SOURCE

| | |
|-------------------------|---------|
| Lighting efficiency | 89% |
| Delivered luminous flux | 1015 Lm |
| Light beam angle | 34° |

LIGHTING FIXTURE | PHOTOMETRIC DATA

LIGHTING FIXTURE | ELECTRICAL DATA

| | |
|----------------------------|--------|
| Power values of the system | 8,50 W |
| Dimming | DALI |


OTHER DATA

| | |
|------------------------|-----------------------------------|
| Environmental location | DAMP |
| Swivel angle | 310° |
| Rotation angle | 360° |
| Track type | Track 48V |
| Weight | 0.36 lb 164 gr |
| Packaged weight | 0.46 lb 210 gr |
| Packaging dimensions | 7.48x5.71x0.94 in 190x145x24 mm |
| Materials | Aluminium - Polycarbonate |



Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM

