



### DIMENSIONS



### ACCESSORIES



TRACK 48V OPTIONS

### AWARDS



<b>Name</b>	SIX S 48V SHORT UL DIM 0/10V 34° 4000K WTW
<b>Reference</b>	U3330132WTW-S
<b>Color</b>	Textured white - White track
<b>Category</b>	Track Lights

### PRODUCT

<b>Type</b>	LED
<b>Gross luminous flux</b>	1210 Lm
<b>Color temperature</b>	4000 K
<b>Chromatic stability</b>	MacAdam Step 2
<b>Color Rendering Index</b>	CRI>90
<b>Power</b>	9 W
<b>Efficacy</b>	134 Lm/W
<b>LED lifespan</b>	L80B10>60.000h

### LIGHT SOURCE

<b>Lighting efficiency</b>	89%
<b>Delivered luminous flux</b>	1077 Lm
<b>Light beam angle</b>	34°

### LIGHTING FIXTURE | PHOTOMETRIC DATA

### LIGHTING FIXTURE | ELECTRICAL DATA

<b>Power values of the system</b>	8,50 W
<b>Dimming</b>	0-10V

### OTHER DATA

<b>Environmental location</b>	DAMP
<b>Swivel angle</b>	310°
<b>Rotation angle</b>	360°
<b>Track type</b>	Track 48V
<b>Weight</b>	0.36 lb   164 gr
<b>Packaged weight</b>	0.46 lb   210 gr
<b>Packaging dimensions</b>	7.48x5.71x0.94 in   190x145x24 mm
<b>Materials</b>	Aluminium - Polycarbonate



Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM

