




DIMENSIONS



ACCESSORIES



TRACK 48V OPTIONS

AWARDS



| | |
|-----------|--|
| Name | SIX XS 48V SHORT UL DIM DALI 23° 2700K NTW |
| Reference | U3350220NTW-S |
| Color | Textured black - White track |
| Category | Track Lights |

PRODUCT

| | |
|-----------------------|----------------|
| Type | LED |
| Gross luminous flux | 470 Lm |
| Color temperature | 2700 K |
| Chromatic stability | MacAdam Step 2 |
| Color Rendering Index | CRI>90 |
| Power | 4.5 W |
| Efficacy | 104 Lm/W |
| LED lifespan | L90B10>55.000h |

LIGHT SOURCE

| | |
|-------------------------|--------|
| Lighting efficiency | 86% |
| Delivered luminous flux | 404 Lm |
| Light beam angle | 23° |

LIGHTING FIXTURE | PHOTOMETRIC DATA

| | |
|----------------------------|--------|
| Power values of the system | 5,00 W |
| Dimming | DALI |

LIGHTING FIXTURE | ELECTRICAL DATA


| | |
|------------------------|-----------------------------------|
| Environmental location | DAMP |
| Swivel angle | 310° |
| Rotation angle | 360° |
| Track type | Track 48V |
| Weight | 0.25 lb 112 gr |
| Packaged weight | 0.35 lb 160 gr |
| Packaging dimensions | 7.48x5.71x0.94 in 190x145x24 mm |
| Materials | Aluminium - Polycarbonate |

OTHER DATA



Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM

