


Black Foster Surface Remote



DIMENSIONS



PRODUCT

Name	BLACK FOSTER SURFACE REMOTE 15 UL FLOOD 4000K WTW
Reference	U4806002WTW
Color	Textured white

LIGHT SOURCE

Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10> 102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	92%
Delivered luminous flux	0 Lm
Light beam angle	38°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Requires remote driver
Power values of the system	W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories

OTHER DATA

Environmental location	DAMP
Weight	2.292 lb 1040 gr
Packaged weight	2.513 lb 1140 gr
Packaging dimensions	27.4 x 3 x 1.7 in 698 x 77 x 44 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




An unostentatious feature in the space. This is how the new Black Foster Surface Remote version reveals its compact and essential lighting fixture. The commitment to the use of a remote driver enables minimising its profile to the extent necessary to integrate its invisible light optical system.


Lighting Technical Data



POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-13.1	-12.5	-12.9	-12.3	-12.1	-14.0	-13.4	-13.8	-13.2	-13.0
	3H	-6.8	-6.2	-6.5	-6.0	-5.8	-6.7	-6.1	-6.4	-5.9	-5.7
	4H	-3.3	-2.8	-3.0	-2.5	-2.3	-2.8	-2.2	-2.5	-2.0	-1.7
	6H	0.3	0.8	0.7	1.1	1.4	0.7	1.2	1.0	1.5	1.8
	8H	2.2	2.7	2.5	3.0	3.2	2.5	3.0	2.8	3.3	3.6
4H	12H	4.2	4.6	4.5	4.9	5.2	4.5	5.0	4.9	5.3	5.6
	2H	-10.6	-10.0	-10.3	-9.8	-9.5	-10.9	-10.4	-10.6	-10.1	-9.9
	3H	-4.6	-4.1	-4.2	-3.8	-3.5	-4.4	-4.0	-4.1	-3.6	-3.3
	4H	-1.2	-0.8	-0.8	-0.4	-0.1	-0.7	-0.3	-0.4	0.0	0.3
	6H	2.4	2.7	2.8	3.1	3.5	2.7	3.0	3.1	3.4	3.8
8H	8H	4.3	4.6	4.7	4.9	5.3	4.5	4.8	4.9	5.2	5.6
	12H	6.3	6.6	6.7	7.0	7.4	6.6	6.9	7.1	7.3	7.7
	4H	0.4	0.7	0.8	1.0	1.4	0.7	0.9	1.1	1.3	1.7
	6H	4.0	4.2	4.5	4.7	5.1	4.2	4.4	4.7	4.9	5.3
	8H	6.0	6.2	6.5	6.6	7.1	6.2	6.4	6.7	6.8	7.3
12H	12H	8.2	8.3	8.6	8.8	9.3	8.4	8.6	8.9	9.0	9.5
	4H	0.9	1.1	1.3	1.5	2.0	1.1	1.4	1.6	1.8	2.2
	6H	4.6	4.8	5.1	5.2	5.7	4.8	5.0	5.2	5.4	5.9
	8H	6.7	6.8	7.2	7.3	7.8	6.9	7.0	7.3	7.5	8.0
Variation of the observer position for the luminaire distances S											
S = 1.0H S = 1.5H S = 2.0H		+0.9 / -0.3 +1.9 / -0.6 +3.1 / -0.8					+1.3 / -0.4 +2.7 / -0.7 +4.2 / -1.0				
Standard table		---					---				
Correction		---					---				
Summand		---					---				
Corrected Glare Indices referring to 3750lm Total Luminous Flux											