



### DIMENSIONS



### ACCESSORIES



TRACK 48V OPTIONS

### AWARDS



|           |  |
|-----------|--|
| Name      | SIX XS 48V SHORT UL DIM 0/10V 23° 4000K NT |
| Reference | U3350122NT-S                               |
| Color     | Textured black                             |
| Category  | Track Lights                               |

### PRODUCT

|                       |                |
|-----------------------|----------------|
| Type                  | LED            |
| Gross luminous flux   | 530 Lm         |
| Color temperature     | 4000 K         |
| Chromatic stability   | MacAdam Step 2 |
| Color Rendering Index | CRI>90         |
| Power                 | 4.5 W          |
| Efficacy              | 118 Lm/W       |
| LED lifespan          | L90B10>55.000h |

### LIGHT SOURCE

|                         |        |
|-------------------------|--------|
| Lighting efficiency     | 86%    |
| Delivered luminous flux | 456 Lm |
| Light beam angle        | 23°    |

### LIGHTING FIXTURE | PHOTOMETRIC DATA

|                            |        |
|----------------------------|--------|
| Power values of the system | 5,00 W |
| Dimming                    | 0-10V  |

### LIGHTING FIXTURE | ELECTRICAL DATA

|                        |   |
|------------------------|---|
| Environmental location | DAMP                                      |
| Swivel angle           | 310°                                      |
| Rotation angle         | 360°                                      |
| Track type             | Track 48V                                 |
| Weight                 | 0.25 lb   112 gr                          |
| Packaged weight        | 0.35 lb   160 gr                          |
| Packaging dimensions   | 7.48 x 5.71 x 0.94 in   190 x 145 x 24 mm |
| Materials              | Aluminium - Polycarbonate                 |

### OTHER DATA



Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM

